

DC FAN

JAMICON®

60X60X15 mm

JF0615-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS															
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)				
JF0615B5HR00	Dual Ball	5	4.25 ~ 5.75	15.45	0.165	4500	0.25	1.25	0.26	30.5	45				
JF0615B5MR00				13.58	0.140	4000	0.20	1.00	0.21	28.8					
JF0615B5L-00				11.86	0.107	3500	0.17	0.85	0.17	25.4					
JF0615B5E-00				9.82	0.081	3000	0.14	0.70	0.14	21.2					
JF0615B5V-00				8.39	0.059	2500	0.11	0.55	0.11	17.9					
JF0615S5HR00	Sleeve			5	4.25 ~ 5.75	15.45	0.165	4500	0.25	1.25		0.26	30.5		
JF0615S5MR00						13.58	0.140	4000	0.20	1.00		0.21	28.8		
JF0615S5L-00						11.86	0.107	3500	0.17	0.85		0.17	25.4		
JF0615S5E-00						9.82	0.081	3000	0.14	0.70		0.14	21.2		
JF0615S5V-00						8.39	0.059	2500	0.11	0.55		0.11	17.9		
JF0615B1UR00	Dual Ball	12	10.2 ~ 13.8			18.87	0.220	5500	0.15	1.80		0.16	37.5		
JF0615B1SR00						17.16	0.200	5000	0.14	1.68		0.15	33.7		
JF0615B1H-00						15.45	0.165	4500	0.13	1.56		0.17	30.5		
JF0615B1M-00						13.58	0.140	4000	0.11	1.32		0.15	28.8		
JF0615B1L-00						11.86	0.107	3500	0.10	1.20		0.12	25.4		
JF0615B1E-00				9.82	0.081	3000	0.08	0.96	0.09	21.2					
JF0615B1V-00				8.39	0.059	2500	0.07	0.84	0.07	17.9					
JF0615S1H-00				Sleeve	12	10.2 ~ 13.8	15.45	0.165	4500	0.14		1.68	0.17	30.5	
JF0615S1M-00							13.58	0.140	4000	0.12		1.44	0.15	28.8	
JF0615S1L-00							11.86	0.107	3500	0.10		1.20	0.12	25.4	
JF0615S1E-00	9.82						0.081	3000	0.08	0.96		0.09	21.2		
JF0615S1V-00	8.39						0.059	2500	0.07	0.84		0.07	17.9		
JF0615B2UR00	Dual Ball			24			20.4 ~ 27.6	18.87	0.220	5500		0.11	2.64	0.12	37.5
JF0615B2SR00								17.16	0.200	5000		0.10	2.40	0.11	33.7
JF0615B2H-00								15.45	0.165	4500		0.12	2.88	0.13	30.5
JF0615B2M-00								13.58	0.140	4000		0.11	2.64	0.11	28.8
JF0615B2L-00								11.86	0.107	3500		0.09	2.16	0.09	25.4
JF0615B2E-00								9.82	0.081	3000		0.05	1.20	0.06	21.2
JF0615B2V-00								8.39	0.059	2500		0.04	0.96	0.04	17.9
JF0615S2H-00								Sleeve	24	20.4 ~ 27.6		15.45	0.165	4500	0.13
JF0615S2M-00		13.58	0.140								4000	0.11	2.64	0.11	28.8
JF0615S2L-00		11.86	0.107								3500	0.09	2.16	0.09	25.4
JF0615S2E-00	9.82	0.081	3000								0.06	1.44	0.06	21.2	
JF0615S2V-00	8.39	0.059	2500								0.04	0.96	0.04	17.9	

Specifications subject to change without notice

