

DC FAN

JAMICON®

60X60X25 mm

JF0625-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS														
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)			
JF0625B1TR00	Dual Ball	12	10.2 ~ 13.8	29.69	0.422	6000	0.37	4.44	0.38	42.5	65			
JF0625B1UR00				26.96	0.357	5500	0.29	3.48	0.30	39.6				
JF0625B1SR00				24.27	0.292	5000	0.22	2.64	0.22	35.7				
JF0625B1H-00				21.44	0.237	4500	0.20	2.40	0.23	34.1				
JF0625B1M-00				19.00	0.185	4000	0.16	1.92	0.20	31.3				
JF0625B1L-00				16.76	0.145	3500	0.13	1.56	0.17	27.3				
JF0625B1E-00				14.24	0.108	3000	0.11	1.32	0.11	22.4				
JF0625B1V-00				11.72	0.076	2500	0.08	0.96	0.08	20.2				
JF0625C1H-00				Ball Sleeve	12	10.2 ~ 13.8	21.44	0.237	4500	0.20		2.40	0.23	34.1
JF0625C1M-00							19.00	0.185	4000	0.16		1.92	0.20	31.3
JF0625S1SR00	Sleeve	12	10.2 ~ 13.8	24.27	0.292	5000	0.22	2.64	0.22	35.7				
JF0625S1H-00				21.44	0.237	4500	0.21	2.52	0.23	34.1				
JF0625S1M-00				19.00	0.185	4000	0.16	1.92	0.20	31.3				
JF0625S1L-00				16.76	0.145	3500	0.13	1.56	0.17	27.3				
JF0625S1E-00				14.24	0.108	3000	0.11	1.32	0.11	22.4				
JF0625S1V-00				11.72	0.076	2500	0.08	0.96	0.08	20.2				
JF0625B2TR00				Dual Ball	24	20.4 ~ 27.6	29.69	0.422	6000	0.20		4.80	0.21	42.5
JF0625B2UR00							26.96	0.357	5500	0.16		3.84	0.16	39.6
JF0625B2SR00							24.27	0.292	5000	0.13		3.12	0.14	35.7
JF0625B2H-00							21.44	0.237	4500	0.12		2.88	0.17	34.1
JF0625B2M-00	19.00	0.185	4000				0.11	2.64	0.13	31.3				
JF0625B2L-00	16.76	0.145	3500				0.10	2.40	0.12	27.3				
JF0625B2E-00	14.24	0.108	3000				0.07	1.68	0.07	22.4				
JF0625B2V-00	11.72	0.076	2500				0.06	1.44	0.06	20.2				
JF0625S2SR00	Sleeve	24	20.4 ~ 27.6				24.27	0.292	5000	0.13		3.12	0.14	35.7
JF0625S2H-00							21.44	0.237	4500	0.14		3.36	0.17	34.1
JF0625S2M-00				19.00	0.185	4000	0.11	2.64	0.13	31.3				
JF0625S2L-00				16.76	0.145	3500	0.10	2.40	0.12	27.3				
JF0625S2E-00				14.24	0.108	3000	0.07	1.68	0.07	22.4				
JF0625S2V-00				11.72	0.076	2500	0.06	1.44	0.06	20.2				
JF0625B4U-00				Dual Ball	48	40.8 ~ 60.0	26.96	0.357	5500	0.10	4.80	0.11	39.6	
JF0625B4S-00							24.27	0.292	5000	0.09	4.32	0.09	35.7	
JF0625B4H-00							21.44	0.237	4500	0.07	3.36	0.08	34.1	
JF0625B4M-00							19.00	0.185	4000	0.06	2.88	0.07	31.3	
JF0625B4L-00	16.76	0.145	3500				0.05	2.40	0.06	27.3				
JF0625B4E-00	14.24	0.108	3000				0.04	1.92	0.05	22.4				

Specifications subject to change without notice

