

DC FAN

JAMICON®

70X70X25 mm

JF0725-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)	
JF0725B1SR00	Dual Ball	12	10.2~13.8	37.01	0.263	4000	0.35	4.20	0.37	37.2	74	
JF0725B1H-00				31.86	0.198	3500	0.23	2.76	0.23	34.6		
JF0725B1M-00				27.27	0.145	3000	0.17	2.04	0.18	29.9		
JF0725B1L-00				23.27	0.102	2500	0.10	1.20	0.11	24.2		
JF0725B1E-00	Ball + Sleeve			18.87	0.065	2000	0.08	0.96	0.08	20.9		
JF0725C1SR00				37.01	0.263	4000	0.35	4.20	0.37	37.2		
JF0725C1H-00				31.86	0.198	3500	0.23	2.76	0.23	34.6		
JF0725C1M-00				27.27	0.145	3000	0.17	2.04	0.18	29.9		
JF0725S1SR00	Sleeve			37.01	0.263	4000	0.35	4.20	0.37	37.2		
JF0725S1H-00				31.86	0.198	3500	0.23	2.76	0.23	34.6		
JF0725S1M-00				27.27	0.145	3000	0.18	2.16	0.18	29.9		
JF0725S1L-00				23.27	0.102	2500	0.10	1.20	0.11	24.2		
JF0725S1E-00	Dual Ball	24	20.4 ~27.6	18.87	0.065	2000	0.08	0.96	0.08	20.9		
JF0725B2SR00				37.01	0.263	4000	0.22	5.28	0.23	37.2		
JF0725B2H-00				31.86	0.198	3500	0.15	3.60	0.16	34.6		
JF0725B2M-00				27.27	0.145	3000	0.10	2.40	0.11	29.9		
JF0725B2L-00				23.27	0.102	2500	0.07	1.68	0.07	24.2		
JF0725B2E-00				18.87	0.065	2000	0.05	1.20	0.05	20.9		
JF0725S2H-00				Sleeve	31.86	0.198	3500	0.15	3.60	0.16		34.6
JF0725S2M-00					27.27	0.145	3000	0.10	2.40	0.11		29.9
JF0725S2L-00	23.27				0.102	2500	0.07	1.68	0.07	24.2		
JF0725S2E-00	18.87				0.065	2000	0.05	1.20	0.05	20.9		

Specifications subject to change without notice

